
Johns Manville is providing this draft specification to the user as a courtesy to consider in their determination of the optimal system specification for their project's specific needs. By receiving and considering the general information provided herein, the user agrees Johns Manville makes no warranty or representation regarding its contents, and it will not be relied upon as a substitute for professional engineering, design and/or documentation required by building code, contract, or applicable law. The general information in this draft specification must be reviewed/approved by a project designer before finalization and use. The user/recipient of this general information assumes sole responsibility for its use. Additional information, such as Data Sheets, SDS, Application Guides and other literature on the Johns Manville products identified in this draft specification, can be found at <https://www.jm.com/en/commercial-roofing/>.

SECTION 075216

STYRENE-BUTADIENE-STYRENE (SBS) MODIFIED BITUMINOUS MEMBRANE ROOFING

PART 1 - GENERAL

1.1 SECTION INCLUDES

- A. SBS-modified bituminous membrane roofing.
- B. Roof insulation.

1.2 RELATED SECTIONS

- A. Division 03 Section "Concrete" for concrete.
- B. Division 03 Section "Lightweight Insulating Concrete" for lightweight insulating concrete..
- C. Division 06 Section "Miscellaneous Rough Carpentry" for wood nailers, cants, curbs, and blocking.
- D. Division 07 Section "Sheet Metal Flashing and Trim" for flashings and counter flashings.
- E. Division 22 Section "Storm Drainage Piping Specialties" for roof drains.

1.3 REFERENCES

- A. Roofing Terminology: Refer to the following publications for definitions of roofing work related terms in this Section:
 - 1. ASTM D 1079 "Standard Terminology Relating to Roofing and Waterproofing."
 - 2. Glossary of NRCA's "The NRCA Roofing and Waterproofing Manual."
 - 3. Roof Consultants Institute "Glossary of Building Envelope Terms."
 - 4. International Building Code (IBC)
 - 5. American Society of Civil Engineers (ASCE-7) Minimum Design Loads for Buildings & Other Structures

- B. Sheet Metal Terminology and Techniques: SMACNA “Architectural Sheet Metal Manual.”
- C. Hot Roofing Asphalt: Roofing asphalt heated to temperature recommended by roofing manufacturer to flux modified roofing membrane, measured at the mop cart or mechanical spreader immediately before application.

1.4 DESIGN CRITERIA

- A. General: Installed roofing membrane system shall remain watertight; and resist specified wind uplift pressures, thermally induced movement, and exposure to weather without failure.
- B. Material Compatibility: Roofing materials shall be compatible with one another under conditions of service and application required, as demonstrated by roofing system manufacturer based on testing and field experience.
- C. Installer shall comply with current code requirements based on authority having jurisdiction.
- D. Wind Uplift Performance: Roofing system shall meet the intent of systems that have been successfully tested by a qualified testing and inspecting agency to resist wind uplift pressure calculated in accordance with ASCE 7.
 - 1. Assembly Basis of Design: Florida Building Code
 - a. Listing/Report: FL17013-R24 (non-HVHZ)
 - b. System: LC-A-26
 - c. Maximum Design Pressure: -170 psf
- E. Fire-Test-Response Characteristics: Provide roofing materials with the fire-test-response characteristics indicated as determined by testing identical products per test method below by UL, or another testing and inspecting agency acceptable to authorities having jurisdiction. Materials shall be identified with appropriate markings of applicable testing and inspecting agency.
 - 1. Exterior Fire-Test Exposure: Class A; UL 790, for application and roof slopes indicated.

1.5 SUBMITTALS

- A. Product Data: Manufacturer’s data sheets for each product to be provided.
- B. Detail Drawings: Provide roofing system details and details of attachment to other Work, including:
 - 1. Base flashings and membrane terminations.
 - 2. Tapered insulation, including slopes.
 - 3. Crickets, saddles, and tapered edge strips, including slopes.
 - 4. Insulation fastening and adhesive patterns.
- C. Verification Samples: Provide for each product specified.

- D. Installer Qualifications: A qualified firm that is approved, authorized, or licensed by roofing system manufacturer to install manufacturers product who is eligible to receive manufacturers special warranty.
- E. Maintenance Data: Refer to Johns Manville’s latest published documents on www.JM.com.
- F. Guarantees: Provide manufacturer’s current guarantee specimen.
- G. Roofing sub-contractor shall provide a copy of the final System Assembly Letter issued by Johns Manville Roofing Systems indicating that the products and system to be installed shall be eligible to receive the specified manufacturer's guarantee when installed by a certified JM contractor in accordance with our application requirements, inspected and approved by a JM Technical Representative.
- H. Prior to roofing system installation, roofing sub-contractor shall provide a copy of the Guarantee Application Confirmation document issued by Johns Manville Roofing Systems indicating that the project has been reviewed for eligibility to receive the specified guarantee and registered.

1.6 QUALITY ASSURANCE

- A. Installer Qualifications: Qualified firm that is approved, authorized, or licensed by roofing system manufacturer to install manufacturer's product who is eligible to receive the specified manufacturer's guarantee.
- B. Manufacturer Qualifications: Qualified domestic U.S. owned and based manufacturer that has UL listing and Florida Product Approval or accredited testing agency for roofing system identical to that used for this Project.
- C. Testing Agency Qualifications: An independent testing agency with the experience and capability to conduct the testing indicated, as documented according to ASTM E 329.
- D. Test Reports:
 - 1. Roof drain and leader test or submit plumber’s verification.
 - 2. Core cut, if required.
 - 3. Roof deck fastener pullout test, if required.
- E. Source Limitations: Obtain all components from the single source roofing manufacturer guaranteeing the roofing system. All products used in the system shall be labeled by the single source roofing manufacturer issuing the guarantee.

1.7 DELIVERY, STORAGE, AND HANDLING

- A. Deliver roofing materials in original containers with seals unbroken and labeled with manufacturer's name, product brand name and type, date of manufacture, and directions for storage.

- B. Store liquid materials in their original undamaged containers in a clean, dry, protected location and within the temperature range required by roofing system manufacturer.
- C. Protect roof insulation materials from physical damage and from deterioration by sunlight, moisture, soiling, and other sources. Comply with insulation manufacturer's written instructions for handling, storing, and protecting during installation.
- D. Handle and store roofing materials and place equipment in a manner to avoid permanent deflection of deck.

1.8 PROJECT CONDITIONS

- A. Weather Limitations: Proceed with installation only when current and forecasted weather conditions permit roofing system to be installed in accordance with manufacturer's written instructions and guarantee requirements.

1.9 GUARANTEE

- A. Provide manufacturer's system guarantee equal to Johns Manville's Peak Advantage No Dollar Limit Roofing System Guarantee.
 - 1. Single-source special guarantee includes roofing plies, base flashings, liquid applied flashing, roofing membrane accessories, roofing membrane, roof insulation, adhesives, walkway products, manufacturer's edge metal products, and other approved single-source components of roofing system marketed by the manufacturer.
 - 2. Guarantee Period: 20 years from date of Substantial Completion.
- B. Installer's Guarantee: Submit roofing Installer's guarantee, signed by Installer, covering Work of this Section, including all components of roofing system, for the following guarantee period:
 - 1. Guarantee Period: two years from date of Substantial Completion.
- C. Existing Guarantees: Guarantees on existing building elements should not be affected by scope of work.
 - 1. Installer is responsible for coordinating with building owner's representative to verify compliance.

PART 2 - PRODUCTS

2.1 BASE PLY AND CAP-SHEET MATERIALS

- A. Roofing Membrane Base Sheet: SBS-modified asphalt sheet; smooth surfaced; suitable for application method specified.

1. ASTM D 6164, Grade S, Type I, polyester-reinforced, Basis of design: DynaBase PR
 PBCFR New Station 24 (SBS) MODIFIED BITUMINOUS ROOFING
 PBC. Project No. 2022-009616
 CSA Project No. 230103

284621 -

- B. Roofing Membrane inner ply sheet: Glass-Fiber Felts 3 plys
 - 1. ASTM D 2178, Type VI, asphalt-impregnated, glass-fiber felt. Basis of design: GlasPly Premier.
- C. Roofing Membrane Cap Sheet: SBS-modified asphalt sheet; granular surfaced; suitable for application method specified.
 - 1. ASTM D 6164, Grade G, Type II, polyester-reinforced, Basis of design: DynaLastic 250 FR CR G.
 - 2. CRRC-listed, highly reflective, non-coated, granular surface with the following minimum properties: Initial SRI- 86, 3 Year SRI- 80

2.2 FLASHING SHEET MATERIALS

- A. Backer Sheet: SBS-modified asphalt sheet; smooth surfaced; suitable for application method specified.
 - 1. ASTM D 6164, Grade S, Type I, polyester-reinforced, Basis of design: DynaBase PR.
- B. Flashing Sheet: SBS-modified asphalt sheet; granular surfaced; suitable for application method specified.
 - 1. ASTM D 6164, Grade G, Type II, polyester-reinforced, Basis of design: DynaLastic 250 FR CR G.
- C. Liquid Applied Flashing: A liquid and fabric reinforced flashing system created with a stitch bonded polyester scrim and a two-component, moisture cured, elastomeric, liquid applied flashing material, consisting of an asphalt extended urethane base material and an activator. Basis of design: PermaFlash System

2.3 AUXILIARY ROOFING MATERIALS

- A. General: Auxiliary materials recommended by roofing system manufacturer for intended use and compatible with built-up roofing.
- B. Roofing Asphalt: ASTM D 312-15, Type IV.
- C. Asphalt Primer: ASTM D 41. Basis of design: JM Asphalt Primer
- D. Asphalt Roofing Cement: ASTM D 4586, type I, asbestos free, of consistency required by roofing system manufacturer for application. Basis of design: MBR Utility Cement
- E. Mastic Sealant: As required by Johns Manville.
- F. Cold-Applied Adhesive: Solvent-Free, Moisture Curing: DynaSet 1K
- G. Roofing Granules: Ceramic-coated roofing granules matching specified cap sheet, provided by roofing system manufacturer. CR Roofing Granules

- H. Miscellaneous Accessories: Provide miscellaneous accessories recommended by roofing system manufacturer.

2.4 WALKWAYS

- A. Walkway Pads: Mineral-granule-surfaced, reinforced modified asphalt composition, slip-resisting pads, manufactured as a traffic pad for foot traffic provided by roofing system manufacturer, with a pad size of 32-inch x 32-inch. Basis of design: DynaTred Walkway

2.5 ROOF INSULATION

- A. General: Provide preformed roof insulation boards that comply with requirements and referenced standards, selected from manufacturer's standard sizes and of thicknesses indicated.
- B. Lightweight insulating concrete in accordance with Section 03 52 16 – Lightweight Insulating Concrete

2.6 EDGE METAL COMPONENTS

- A. Metal Flashing Sheet: Metal flashing sheet is specified in Division 07 Section "Sheet Metal Flashing and Trim."
- B. Roof Edge Drainage Systems: Gutter Systems: Manufactured in section lengths not exceeding 12 feet with 0.100-inch mill aluminum internal Gutter Hangers, 24 inches on center, and 2-inch-wide formed external wind straps 6'-0" on center

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, areas, and conditions for compliance with the requirements affecting performance of roofing system.
 - 1. General:
 - a. Verify that roof openings and penetrations are in place and set and braced and that roof drains are securely clamped in place.
 - b. Verify that wood cants, blocking, curbs, and nailers are securely anchored to roof deck at penetrations and terminations and that nailers match thicknesses of insulation.
 - 2. Concrete Decks:
 - a. Verify that concrete curing compounds that will impair adhesion of roofing components to roof deck have been removed.
 - b. Verify that concrete substrate is visibly dry and free of moisture.

3. Ensure general rigidity and proper slope for drainage.
 4. Verify that deck is securely fastened with no projecting fasteners and with no adjacent units more than 1/16 inch (1.6 mm) out of plane relative to adjoining deck.
- B. Unacceptable panels should be brought to the attention of the General Contractor and Project Owner's Representative and shall be corrected prior to installation of roofing system.
- C. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Clean and remove from substrate sharp projections, dust, debris, moisture, and other substances detrimental to roofing installation in accordance with roofing system manufacturer's written instructions.
- B. Prevent materials from entering and clogging roof drains and conductors and from spilling or migrating onto surfaces of other construction.
- C. If applicable, prime surface of deck with primer at a rate recommended by roofing manufacturer and allow primer to dry.
- D. Proceed with each step of installation only after unsatisfactory conditions have been corrected.

3.3 ROOFING MEMBRANE INSTALLATION, GENERAL

- A. Install roofing membrane in accordance with roofing system manufacturer's written instructions, applicable recommendations of the roofing manufacturer and requirements in this Section.
- B. Cooperate with testing and inspecting agencies engaged or required to perform services for installing roofing system.
- C. Where roof slope exceeds 1/2 inch per 12 inches (1:24), contact the membrane manufacturer for installation instructions regarding installation direction and backnailing
- D. Coordinate installing roofing system so insulation and other components of the roofing membrane system not permanently exposed are not subjected to precipitation or left uncovered at the end of the workday or when rain is imminent.
1. Provide tie-offs at end of each day's work to cover exposed roofing membrane sheets and insulation.
 2. Complete terminations and base flashings and provide temporary seals to prevent water from entering completed sections of roofing system.
 3. Remove and discard temporary seals before beginning work on adjoining roofing.
- E. Asphalt Heating: Heat roofing asphalt to temperature recommended by roofing manufacturer to flux modified membrane. Do not exceed roofing asphalt manufacturer's recommended temperature limits during roofing asphalt heating. Discard roofing asphalt maintained at a temperature exceeding finished blowing temperature for more than 4 hours.

- F. Substrate-Joint Penetrations: Prevent roofing asphalt from penetrating substrate joints, entering building, or damaging roofing system components or adjacent building construction.

3.4 SBS-MODIFIED BITUMINOUS MEMBRANE INSTALLATION

- A. Install base sheet, three bituminous roofing membrane plys, and cap sheet according to roofing manufacturer's written instructions, starting at low point of roofing system. Extend roofing membrane sheets over and terminate beyond cants, with the following installation method:
 - 1. Unroll roofing membrane sheets and allow them to relax.
 - 2. Adhere [modified bituminous roofing membrane plys and cap sheet to substrate in a solid mopping of hot roofing asphalt applied at temperatures recommended by roofing system manufacturer.
 - 3. Adhere modified bituminous roofing membrane base sheet to substrate in cold-applied adhesive according to roofing system manufacturer's instruction.
- B. Laps: Accurately align roofing membrane sheets, without stretching, and maintain uniform side and end laps. Stagger end laps. Completely bond and seal laps, leaving no voids.
 - 1. Repair tears and voids in laps and lapped seams not completely sealed.
 - 2. As required, apply roofing granules to cover exuded bead at laps while bead is hot.
- C. Install roofing membrane sheets so side and end laps shed water.

3.5 FLASHING AND STRIPPING INSTALLATION

- A. Install base flashing over cant strips and other sloping and vertical surfaces, at roof edges, and at penetrations through roof, and secure to substrates according to roofing system manufacturer's written instructions and as follows:
 - 1. Prime substrates with asphalt primer if required by roofing system manufacturer.
 - 2. Backer Sheet Application: Mechanically fasten backer sheet to walls or parapets.
 - 3. Backer Sheet Application: Adhere backer sheet to substrate in a solid mopping of hot roofing asphalt.
 - 4. Flashing Sheet Application Adhere flashing sheet to substrate in a solid mopping of hot roofing asphalt. Apply hot roofing asphalt to back of flashing sheet as required by roofing system manufacturer.
- B. Extend base flashing up walls or parapets 8 inches (200 mm) above roofing membrane. Refer to manufacturer's standard flashing details.
- C. Mechanically fasten top of base flashing securely at terminations and perimeter of roofing.
 - 1. Seal top termination of base flashing with a strip of glass-fiber fabric set in MBR Flashing cement.
- D. Roof Drains: Flash drain using liquid applied flashing system. Clamp roofing membrane, flashing, and stripping into roof-drain clamping ring.

1. Install stripping according to roofing system manufacturer's written instructions.
- E. Flash all penetrations using liquid applied flashing system.

3.6 EDGE METAL INSTALLATION

- A. Examine substrates and conditions under which sheet metal flashing and trim are to be installed and verify that work may properly commence. Do not proceed with installation until unsatisfactory conditions have been corrected.
- B. Provide edge details as indicated on the Drawings. Install in accordance with the membrane manufacturer's requirements and SMACNA's "Architectural Sheet Metal Manual."
- C. Join individual sections in accordance with the membrane manufacturer's requirements and SMACNA's "Architectural Sheet Metal Manual".

3.7 WALKWAY INSTALLATION

- A. Walkway Pads: Install walkway pads using units of size indicated or, if not indicated, of manufacturer's standard size according to walkway pad manufacturer's written instructions.
 1. Sweep away loose aggregate surfacing and set walkway pads in additional flood coat of hot roofing asphalt.
- B. Roof-Paver Walkways: Install walkway roof pavers according to manufacturer's written instructions in locations indicated, to form walkways.

3.8 FIELD QUALITY CONTROL

- A. Final Roof Inspection: Arrange for roofing system manufacturer's technical representative to inspect roofing installation on completion and submit report to Architect.
- B. Repair or remove and replace components of roofing system where test results or inspections indicate that they do not comply with specified requirements.
- C. Additional testing and inspecting, at Contractor's expense, will be performed to determine compliance of replaced or additional work with specified requirements.

3.9 PROTECTION AND CLEANING

- A. Protect roofing system from damage and wear during remainder of construction period.
- B. Correct deficiencies in or remove roofing system that does not comply with requirements, repair substrates, and repair or reinstall roofing system to a condition free of damage and deterioration at time of Substantial Completion and according to warranty requirements.

- C. Clean overspray and spillage from adjacent construction using cleaning agents and procedures recommended by manufacturer of affected construction.

END OF SECTION 075216